

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.01.2022

Version number 8 (replaces version 7)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: UHU AP 35ml FS EN/CS/SK/HU/RU/BG/RO
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

UHU GmbH & Co.KG

Herrmannstraße 7 D-77815 Bühl (Baden)

Tel.:0049-(0)7223-284-0

Fax: 0049-(0)7223-284-245 emaill: sds@boltonadhesives.com

- · Further information obtainable from: UHU QESH
- · 1.4 Emergency telephone number:

Tel.: + 49 (0) 30/19240 (Notruf)

Tel.: + 49 (0) 72 23/28 40

England and Wales (NHS Direct) 111 Schottland (NHS 24) 111

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling: methyl acetate acetone

(Contd. on page 2)

Revision: 15.01.2022

- GB-EN

1/11 www.uhu.com



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.01.2022 Version number 8 (replaces version 7) Revision: 15.01.2022

Trade name: UHU AP 35ml FS EN/CS/SK/HU/RU/BG/RO

(Contd. of page 1)

· Hazard statements

H225 Highly flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing vapours.

P501 Dispose of contents/container in accordance with national regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Adhesive

· Dar	· Dangerous components:		
EIN	S: 79-20-9 IECS: 201-185-2 ex number: 607-021-00-X g.nr.: 01-2119459211-47- XX	methyl acetate The Flam. Liq. 2, H225; The Eye Irrit. 2, H319; STOT SE 3, H336	50-100%
EIN	S: 64-17-5 IECS: 200-578-6 ex number: 603-002-00-5 g.nr.: 01-2119457610-43	ethanol Flam. Liq. 2, H225; Eye Irrit. 2, H319	≥2.5-<10%
EIN	S: 67-64-1 IECS: 200-662-2 ex number: 606-001-00-8 g.nr.: 01-2119471330-49- XX	acetone	≥2.5-<10%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

No special measures required.

- · After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

GB-EN

www.uhu.com 2/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.01.2022 Version number 8 (replaces version 7) Revision: 15.01.2022

Trade name: UHU AP 35ml FS EN/CS/SK/HU/RU/BG/RO

(Contd. of page 2)

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class: 3

(Contd. on page 4)

GB-EN

www.uhu.com 3/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.01.2022 Version number 8 (replaces version 7) Revision: 15.01.2022

Trade name: UHU AP 35ml FS EN/CS/SK/HU/RU/BG/RO

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

79-20-9 methyl acetate

WEL Short-term value: 770 mg/m³, 250 ppm Long-term value: 616 mg/m³, 200 ppm

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

· DNELs

79-20-9 methyl acetate

	=	
Oral		44 mg/kg bw/day
Dermal	Consumer, dermal, longterm exposition	44 mg/kg bw/day
Inhalative	Consumer DNEL, acute inhalation	mg/m³ (rat)
		mg/m³ (rabbit)
	Canalinas inhalation langtages averagition	404 mag/ma3

Consumer, inhalation, longterm exposition 131 mg/m³

64-17-5 ethanol

Oral	Consumer, oral, longterm exposition	87 mg/kg bw/day
Dermal	Consumer, dermal, longterm exposition	343 mg/kg bw/day
Inhalative	Consumer, inhalation, longterm exposition	950 mg/m³

67-64-1 acetone

Oral	Consumer, oral, longterm exposition	62 mg/kg bw/day
Dermal	Consumer, dermal, longterm exposition	62 mg/kg bw/day
Inhalative	Consumer, inhalation, longterm exposition	200 mg/m³

· PNECs

79-20-9 methyl acetate

Fresh water	0.12 mg/l
Marine water	0.012 mg/l
Soil	0.0416 mg/kg

64-17-5 ethanol

Fresh water	0.96 mg/l
Marine water	0.79 mg/l
Soil	0.63 mg/kg

67-64-1 acetone

Fresh water	10.6 mg/l
Marine water	1.06 mg/l

(Contd. on page 5)

GB-EN -

www.uhu.com 4/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.01.2022 Version number 8 (replaces version 7) Revision: 15.01.2022

Trade name: UHU AP 35ml FS EN/CS/SK/HU/RU/BG/RO

(Contd. of page 4)

Soil 29.5 mg/kg

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection: Not required.

Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Recommended thickness of the material: > 0,12 mm

glove material: butyl rubber

thickness of the glove material: 0,6 - 0,8 mm

breakthrough time (maximum wearing time): 60 - 120 min.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
 Colour:
 Odour:
 Odour threshold:
 Melting point/freezing point:
 Fluid
 Colourless
 Characteristic
 Not determined.
 Undetermined.

Boiling point or initial boiling point and

boiling range 55.8-56.6 °C • Flammability Not applicable.

(Contd. on page 6)

GB-EN

www.uhu.com 5/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.01.2022 Version number 8 (replaces version 7) Revision: 15.01.2022

Trade name: UHU AP 35ml FS EN/CS/SK/HU/RU/BG/RO

(Contd. of page 5)

Lower and upper explosion limit

 • Lower:
 3.1 Vol %

 • Upper:
 16 Vol %

 • Flash point:
 -13 °C

· **Auto-ignition temperature:** Product is not selfigniting.

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

Kinematic viscosity
 Dynamic at 20 °C:
 Not determined.
 4400 mPas

Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined.

· Vapour pressure at 20 °C: 220 hPa

Density and/or relative density

Density at 20 °C: 0.987 g/cm³
 Relative density Not determined.
 Vapour density Not determined.

• 9.2 Other information All relevant physical data were determined for the

mixture. All non-determined data are not measurable or not relevant for the

characterization of the mixture.

· Appearance:

· Form: Fluid

Important information on protection of health

and environment, and on safety.

Ignition temperature: 425 °C

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

Organic solvents: 65.8 %
 Water: 0.4 %
 VOC (EC) 65.79 %
 Solids content: 33.8 %

· Change in condition

· Evaporation rate Not determined.

Information with regard to physical hazard

classes

Explosives
Flammable gases
Aerosols
Oxidising gases
Gases under pressure

Void
Void

• Flammable liquids Highly flammable liquid and vapour.

Flammable solids
Self-reactive substances and mixtures
Pyrophoric liquids
Pyrophoric solids
Void
Void

(Contd. on page 7)

GB-EN

www.uhu.com 6/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.01.2022 Version number 8 (replaces version 7) Revision: 15.01.2022

Trade name: UHU AP 35ml FS EN/CS/SK/HU/RU/BG/RO

(Contd. of page 6)

		,
· Self-heating substances and mixtures · Substances and mixtures, which emit	Void	
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
· Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification: 79-20-9 methyl acetate Oral LD50 3705 mg/kg (rabbit) 64-17-5 ethanol LD50 7060 mg/kg (rat) Oral Inhalative LC50/4 h 20000 mg/l (rat) 67-64-1 acetone Oral LD50 5800 mg/kg (rat) LD50 Dermal 20000 mg/kg (rabbit)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.

(Contd. on page 8)

GB-EN

www.uhu.com 7/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.01.2022 Version number 8 (replaces version 7) Revision: 15.01.2022

Trade name: UHU AP 35ml FS EN/CS/SK/HU/RU/BG/RO

(Contd. of page 7)

- · Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR/ADN, IMDG, IATA UN1133

14.2 UN proper shipping name

· ADR/ADN 1133 ADHESIVES

(Contd. on page 9)

GR-EN

www.uhu.com 8/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.01.2022 Version number 8 (replaces version 7) Revision: 15.01.2022

Trade name: UHU AP 35ml FS EN/CS/SK/HU/RU/BG/RO

IMDG, IATA	ADHESIVES
14.3 Transport hazard class(es)	
ADR/ADN	
Class	3 (F1) Flammable liquids.
Label	3
IMDG, IATA	
Class Label	3 Flammable liquids.
14.4 Packing group	
· ADR/ADN, IMDG, IATA	III
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code): EMS Number:	
Stowage Category	F-E,S-D A
14.7 Maritime transport in bulk according to	
IMO instruments	Not applicable.
Transport/Additional information:	
Quantity limitations	On passenger aircraft/rail: 60 L
ADD/ADN	On cargo aircraft only: 220 L
ADR/ADN Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 m
	Maximum net quantity per outer packaging: 100 ml
Transport category	3
Tunnel restriction code	E
· IMDG	EI.
Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1
,	Maximum net quantity per inner packaging: 30 m
	Maximum net quantity per outer packaging: 100 ml
	(Contd. on page 2

www.uhu.com 9/11

- GB-EN -



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.01.2022 Version number 8 (replaces version 7) Revision: 15.01.2022

Trade name: UHU AP 35ml FS EN/CS/SK/HU/RU/BG/RO

(Contd. of page 9)

UN "Model Regulation":

UN 1133 ADHESIVES, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

67-64-1 acetone

· Regulation (EC) No 273/2004 on drug precursors

67-64-1 acetone

3

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

67-64-1 acetone

3

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Classification according to Regulation (EC) No 1272/2008		
Flammable liquids	Bridging principles	
	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.	

· Department issuing SDS: UHU QESH

· Contact: UHU QESH

(Contd. on page 11)

GB-EN -

www.uhu.com 10/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.01.2022 Version number 8 (replaces version 7) Revision: 15.01.2022

Trade name: UHU AP 35ml FS EN/CS/SK/HU/RU/BG/RO

(Contd. of page 10)

Date of previous version: 12.01.2022 · Version number of previous version: 7

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.

GB-EN

11/11 www.uhu.com